

103850

Microwave Sensor IP65

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Frosted & white ABS plastic finish
- Constructed from ABS plastic
- Complete with built in photocell & PIR
- 10 lux On, 50 lux Off. 150° detection angle, 6m maximum range with a 5 second to 30 min timer function
- IP65

SPEC DATA

| | |
|------------------------|---|
| Voltage: | 220-240V 50Hz a.c. |
| Load: | 400W (inductive), 800W (resistive) |
| HF System: | 5.8GHz±75MHz, ISM wave band |
| Transmitting Power: | <0.5mW |
| Power Consumption: | ≤0.5W (standby) |
| Detection zone: | Max. (D x H): 12m x 10m |
| Detection sensitivity: | 25% / 50% / 75% / 100% |
| Hold Time: | 5s / 30s / 1min / 3mins / 20mins / 30 mins |
| Daylight sensor: | 2Lux / 10Lux / 25Lux / 50Lux / 100Lux / Disable |
| Daylight open/close: | 10Lux / 50Lux; 25Lux / 75Lux; 50Lux / 100Lux; 100Lux / 200Lux; 150Lux / 300 Lux; Disable. |
| Mounting height: | 6m Max. |
| Motion detection: | 0.5~3m/s |
| Detection angle: | 150° (wall installation) / 360° (ceiling installation) |
| Operating temperature: | -25°C to +60°C |

