

ORBITAL RANGE

SLIM DIE CAST ALUMINIUM DOME
Ideal for shallow ceiling voids

UNIQUE PATENTED
TECHNOLOGY

LENS FREE
No visible light source from unique anti-glare dome

120° BEAM ANGLE

LED CIRCLE
Project light into the dome, bouncing indirect light into the room

BEZEL FINISH
Chrome, satin nickel & matt white*

LENS FREE

No visible light source from unique anti-glare dome



FAST FIX

Quick installation with the loop-in loop-out four-way connector box



EAGLERISE DRIVER

included



EAGLERISE

INSULATION COVER

Directly cover over with insulation whilst fitting in shallow ceilings voids.



ORBITALPLUS

The OrbitalPlus family is a range of slimline recessed downlights which are fire rated and IP65 rated. Its anti-glare dome projects 460 lumens of warm or cool white light. This unique and patented design can be covered with insulation and fits into shallow ceiling voids. Supplied with a dimmable Eaglerise driver, it is available with warm white or cool white LEDs and in three finishes, Satin nickel, Chrome and Matt white.



IP65
RATED

FIRE
RATED


DIMMABLE

EAGLERISE
DRIVER

A MEMBER OF
ACID
ANTI-COPYING IN DESIGN



- Constructed from die cast aluminium alloy & steel
- 9W LED module (SMD)
- Min. void 55mm
- Compatible dimmer 75021 (150W), see page 300
- Compatible emergency kit 92514 & 91944, see page 280/281



Can be covered with insulation

CODE	DESCRIPTION	FINISH	K	LM	LM/W	DIMENSIONS	CUT OUT
69880	OrbitalPLUS	Matt white	3000	460	51	Proj: 2mm H: 42mm Dia: 110mm	Dia: 97mm
69883	OrbitalPLUS	Matt white	5000	460	51	Proj: 2mm H: 42mm Dia: 110mm	Dia: 97mm
69881	OrbitalPLUS	Satin nickel	3000	460	51	Proj: 2mm H: 42mm Dia: 110mm	Dia: 97mm
69884	OrbitalPLUS	Satin nickel	5000	460	51	Proj: 2mm H: 42mm Dia: 110mm	Dia: 97mm
69882	OrbitalPLUS	Chrome plate	3000	460	51	Proj: 2mm H: 42mm Dia: 110mm	Dia: 97mm
69885	OrbitalPLUS	Chrome plate	5000	460	51	Proj: 2mm H: 42mm Dia: 110mm	Dia: 97mm