ORBITALPRO

Using the latest in Colour Changing Technology (CCT), each OrbitalPRO can be warm white or cool white with a simple flick of a switch. The two sets of SMD LED modules project 450 - 990 lumens of indirect LED light from the unique anti-glare dome. The slim line, patented design is fire rated, IP65 rated and can be covered with insulation, whilst fitting into shallow ceiling voids. Supplied with a dimmable Eaglerise driver that works with leading and trailing edge dimmers. Fitted with a 4-way toolless push fit terminal block for ease of install. Comes in a Matt white finish.



CODE	DESCRIPTION						DIMENSIONS	
90954	NEW OrbitalPRO CCT 9W	A	Matt white	3000/4000/6000	450	50	Proj: 3mm H: 42mm Dia: 110mm	Dia: 97mm
71512	OrbitalPRO CCT 12W	Α	Matt white	3000/5000	700	58	Proj: 3mm H: 42mm Dia: 135mm	Dia: 125mm
71515	OrbitalPRO CCT 15W	Α	Matt white	3000/5000	990	66	Proj: 3mm H: 45mm Dia: 165mm	Dia: 155mm


ORBITAL SMART

The Orbital Smart boasts two sets of SMD LED modules project 450 lumens of indirect LED light from the unique anti-glare dome. The slim line, patented design is fire rated, IP65 rated and can be covered with insulation, whilst fitting into shallow ceiling voids. Fitted with a push fit tool-less terminal block and male/female connector for ease of install. This smart fitting can all be controlled via the SaxbySmart app or using voice activation via Amazon Alexa or Google Home, allowing you ultimate control, whether it's changing colour temperature, dimming or switching on and off.





Constructed from die cast aluminium alloy & steel9W LED module (SMD) CCT



SaxbySmart is compatible with Amazon Echo and Google Home allowing you to control the lights directly using your own voice.







CODE	DESCRIPTION						CUT OUT
79305	Orbital Smart 9W	Matt white	3000/6000	450	50	Proj: 3mm H: 42mm Dia: 110mm	Dia 97mm

26 RECESSED FIRE RATED RECESSED FIRE RATED 27