



AFRWOLED/220/CW

Fresno LED Adjustable Inground Uplight 19W Cool White



Features

High performance LED adjustable inground uplight.

Outperforms 70W CDM-T

304L stainless steel bezel and powder coated aluminium housing.

Supplied c/w installation housing for additional protection and ease of installation.

Integral driver and pre-wired with 2 metres of rubber insulated cable.

Static load test to 2000kg and therefore suitable for vehicular and pedestrian traffic.

LED lifespan L70 36,000 hours

Non-dimmable

General Information

Lamp Type	LED
Colour / Finish	Stainless Steel
IP Rating	IP67
IK Rating	IK10
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Recessed
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	220
Depth (mm)	218

Technical Information

Wattage	20W
Lumens Delivered	1076lm
Lm/W	54lm
Beam Angle	15
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-20 to 40°C

Technical Data - ETIM - In-ground luminaire (EC000758)

With light source	Yes
Suitable for number of lamps	1
Colour housing	Stainless steel
Nominal voltage	230-230 V
Control gear included	Yes
No dim function	Yes
Adjustable	Yes
Beam angle	Narrow beam 11-20°
Degree of protection (IP)	IP67
Protection class	I
Max. system power	20 W
Rated luminous flux acc. IEC 62722-2-1	1076 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Height/depth	218 mm
Outer diameter	220 mm
Max. load	2000 kg
Over rollable	Yes

Datasheet generated from <https://onetimepim.com> last updated Tuesday, June 23, 2020 10:36:56 AM

